



CRESTAKYD[®] 30-5034

Short oil alkyd

INTRODUCTION CRESTAKYD 30-5034 is a low colour short oil alkyd used primarily for wood coatings.

CHARACTERISTICS (Not to be taken as a specification)

Appearance		Clear, bit free
Solids content	%	50
Oil type		Special Fatty Acids
Oil content	%	43
Solvent		Xylene
Acid value (base resin)	mg KOHg ⁻¹	max. 10
Viscosity Brookfield, Spindle 1, 20 rpm @ 25°C	mPa·s	150
Efflux time, DIN cup 4, @ 20°C	seconds	25 – 35
Colour	Gardner	6 max

APPLICATIONS

CRESTAKYD 30-5034 can be used in combination with nitrocellulose sealers and topcoats. The coatings exhibit rapid solvent release and good cold check resistance.

PACKAGING

CRESTAKYD 30-5034 can be supplied in drums. Bulk deliveries are by road tanker.

STORAGE

The resin should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 0°C and 30°C. Exposure to direct sunlight should be avoided.

HEALTH & SAFETY

Please see separate Material Safety Data Sheet.

Issue No. 1

Scott Bader Company Limited
Wollaston, Wellingborough, Northamptonshire, NN29 7RL
Telephone: +44 (0) 1933 663100 Facsimile: +44 (0) 1933 666529

