



Speciality Polymers



TEXICRYL[®] 13-066

Provisional Data Sheet

INTRODUCTION

Texicryl 13-066 is a styrene acrylic copolymer emulsion, designed primarily for the production of flexible, water-resistant ceramic tile adhesives.

Texicryl 13-066 is especially suitable for floor tile adhesives.

Texicryl 13-066 is Alkyl Phenol Ethoxylate free.

CHARACTERISTICS

(Not to be taken as a specification)

Solids content		%	
50			
Viscosity at 25 °C	mPa.s		700
(Brookfield RVT, Spindle 4, 100 rpm)			
pH			
8			
Minimum film formation temperature	°C		0
Particle size		nm	
200			

* Determined by metal bar with temperature gradient

APPROVALS

C.T.A.'s formulated on this product can achieve class AA standard to BS 5980 : 1980 and BS EN 1324.99

APPLICATIONS

Texicryl 13-066 can be compounded into adhesives with a high degree of flexibility for use with wall and floor ceramic tiles.

PACKAGING

Texicryl 13-066 is supplied in 200 kg drums, 1 tonne IBCs or bulk supplies are delivered by road tanker.

STORAGE

Texicryl 13-066 may be stored in the containers in which it is supplied.

Protect from frost and extended exposure to direct sunlight.

HEALTH & SAFETY

Please see separate Material Safety Data Sheet.