

TEXICRYL® 13-073

Silanised Acrylic / Styrene emulsion

INTRODUCTION

TEXICRYL 13-073 is a styrene acrylic copolymer emulsion, designed primarily for the production of flexible, water-resistant ceramic tile adhesives.

TEXICRYL 13-073 is especially suitable for floor tile adhesives.

TEXICRYL 13-073 is Alkyl Phenol Ethoxylate free.

CHARACTERISTICS (Not to be taken as a specification)

Solids Content	%	50
Viscosity at 25°C (Brookfield RVT, Spindle 4, 100 rpm)	mPa s	750
pН		8
Particle size	nm	130
Minimum film formation temperature*	°C	0

^{*} Determined by metal bar with temperature gradient.

APPLICATIONS TEXICRYL 13-073 can be compounded into adhesives with a

high degree of flexibility for use with wall and floor ceramic

tiles.

PACKAGING TEXICRYL 13-073 is supplied in 200 kg drums, 1 tonne IBC's

or bulk supplies are delivered by road tanker.

STORAGE TEXICRYL 13-073 may be stored in the containers in which it

is supplied.

Protect from frost and extended exposure to direct sunlight.

HEALTH & SAFETY Please see separate Material Safety Data Sheet.

Issue No.2





