



TEXICRYL[®] 13-309

Carboxylated acrylic copolymer emulsion

INTRODUCTION

TEXICRYL 13-309 is a carboxylated acrylic copolymer emulsion designed for use as a thickener in emulsion paints and for thickening various adhesive compounds.

TEXICRYL 13-309 can be used to enhance the adhesion, flexural and tensile strength in cementitious screeds.

CHARACTERISTICS

(Not to be taken as a specification)

Solids content	%	35 ± 1
Viscosity at 25°C (Brookfield RVT, Spindle 2, 100 rpm)	cps	50
pH		3
MFFT*	°C / °F	10 / 50
Tg	°C / °F	42 / 107

**Determined by metal bar with temperature gradient.*

APPLICATIONS

TEXICRYL 13-309 is a thickener for use in artist's paints, adhesives and textile coatings. Texicryl 13-309 helps balance rheological properties of a paint and aids application / flow properties.

PACKAGING

TEXICRYL 13-309 is supplied in a 264 lb. net weight plastic drum. Bulk supplies are delivered by road tanker.

STORAGE

TEXICRYL 13-309 may be stored in the containers in which it is supplied.
Protect from temperatures below 40°F.

HEALTH & SAFETY

Please see separate Material Safety Data Sheet.

10/12

NOTICE

The information and recommendations in this publication are, to the best of our actual knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of Scott Bader, Inc. and users of these products should make their own tests to determine the suitability of these products for their own particular purposes. Because of numerous factors beyond our control affecting the results of the use of these products, SCOTT BADER, INC. MAKES NO WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, OTHER THAN THAT THE PRODUCT CONFORMS TO IT'S APPLICABLE CURRENT STANDARD SPECIFICATION.

Suggestions for uses of our products should not be understood as recommending the use of our products in violation of any patent.

7/04