



# TEXICRYL<sup>®</sup> 13-312

## Carboxylated acrylic copolymer emulsion

### INTRODUCTION

**TEXICRYL 13-312** is an alkali swellable thickener designed for waterbased formulations. It is highly effective in producing a very stable viscosity response between pH 6.5 – 10.

### CHARACTERISTICS

(Not to be taken as a specification)

Solids content	%	29 ± 1
Viscosity at 25°C (Brookfield RVT, Spindle 2, 100 rpm)	cps	30
pH		3.5
Particle size	nm	150
Relative density at 25°C		1.05

### APPLICATIONS

**TEXICRYL 13-312** is used in the formulation of textured coatings, construction adhesives, paints and waterborne coating systems.

**PACKAGING**

**TEXICRYL 13-312** is supplied in a 264 lb. net weight plastic drum. Bulk supplies are delivered by road tanker.

**STORAGE**

**TEXICRYL 13-312** may be stored in the containers in which it is supplied. Protect from temperatures below 40°F.

**HEALTH & SAFETY**

Please see separate Material Safety Data Sheet.

10/12

NOTICE

The information and recommendations in this publication are, to the best of our actual knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of Scott Bader, Inc. and users of these products should make their own tests to determine the suitability of these products for their own particular purposes. Because of numerous factors beyond our control affecting the results of the use of these products, SCOTT BADER, INC. MAKES NO WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, OTHER THAN THAT THE PRODUCT CONFORMS TO IT'S APPLICABLE CURRENT STANDARD SPECIFICATION.

Suggestions for uses of our products should not be understood as recommending the use of our products in violation of any patent.

7/04