

TEXICRYL® 13-065

Styrene acrylic copolymer emulsion

INTRODUCTION

TEXICRYL 13-065 is a styrene acrylic copolymer emulsion, designed primarily as a binder for high performance ceramic tile adhesives.

TEXICRYL 13-065 is Alkyl Phenol Ethoxylate free.

CHARACTERISTICS (Not to be taken as a specification)

Solids Content	%	50
Viscosity at 25°C (Brookfield RVT, Spindle 1, 50 rpm)	mPa s	65
pН		8
Particle size	nm	200
Emulsifying system		anionic/non- ionic
MFFT*	°C	26

^{*} Determined by metal bar with temperature gradient.

APPROVAL

C.T.A.'s formulated on this product can achieve EN 12004 : 2001 D2 classification.

APPLICATIONS TEXICRYL 13-065 has been designed to be formulated with a

wide range of filler types into water resistant tile adhesives and

fix and grouts.

PACKAGING TEXICRYL 13-065 is supplied in 200 kg drums, 1 tonne IBC's

or bulk supplies are delivered by road tanker.

STORAGE TEXICRYL 13-065 may be stored in the containers in which it

is supplied.

Protect from frost and extended exposure to direct sunlight.

HEALTH & SAFETY Please see separate Material Safety Data Sheet.

Issue No. 5











