

TEXICRYL® 13-601

Acrylic copolymer emulsion

INTRODUCTION TEXICRYL 13-601 is a pure acrylic copolymer emulsion designed for use

in both interior and exterior coating applications.

CHARACTERISTICS (Not to be taken as a specification)

Solids content	%	49.0 - 51.0
Viscosity at 25°C	cps	0 - 150
(Brookfield RVT,		
Spindle 2, 100 rpm)		
pН		8.0 - 9.0
Particle size	nm	110 - 180
Relative density at 25°C		1.02
MFFT*	°C / °F	0 / 32
Tg	°C / °F	8 / 46

^{*}Determined by metal bar with temperature gradient.

APPLICATIONS TEXICRYL 13-601 can be formulated in solvent free decorative coatings

with excellent durability and low dirt pickup.

Other applications include artist's colours and hobby paints.

PACKAGING TEXICRYL 13-601 is supplied in a 460 lb. net weight plastic drum. Bulk

supplies are delivered by road tanker.

STORAGE TEXICRYL 13-601 may be stored in the containers in which it is supplied.

Protect from temperatures below 40° F.

HEALTH & SAFETY Please see separate Material Safety Data Sheet.

5/10

NOTICE

The information and recommendations in this publication are, to the best of our actual knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of Scott Bader, Inc. and users of these products should make their own tests to determine the suitability of these products for their own particular purposes. Because of numerous factors beyond our control affecting the results of the use of these products, SCOTT BADER, INC. MAKES NO WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, OTHER THAN THAT THE PRODUCT CONFORMS TO IT'S APPLICABLE CURRENT STANDARD SPECIFICATION.

Suggestions for uses of our products should not be understood as recommending the use of our products in violation of any patent.

7/04