

TEXICOTE® 03-084

Polyvinyl acetate homopolymer emulsion

INTRODUCTION

TEXICOTE 03-084 is high viscosity vinyl acetate homopolymer emulsion, stabilised with polyvinyl alcohol. It can be used as an adhesive and adhesive bases in a wide range of applications.

CHARACTERISTICS (Not to be taken as a specification)

Solids Content	%	49 - 52.5
Viscosity at 25°C (Rheomat, Mobil 3, 25 s ⁻¹)	dPa s	32 - 52
pH		4 - 5.5
Minimum film formation temperature*	°C	+ 15
Glass transition temperature	°C	+ 37

^{*} Determined by metal bar with temperature gradient.

APPLICATIONS

TEXICOTE 03-084 is recommended as a base emulsion for wet bond adhesives because of its high viscosity and wet-tack. TEXICOTE 03-084 is also recommended as a base for wood and general purpose adhesives in the building industry and as a cement additive to promote adhesion to sub-floors and improve anti-dusting properties.

PACKAGING TEXICOTE 03-084 may be supplied in drums or IBC's (please

check with your local representative). Bulk deliveries are by

road tanker.

STORAGE TEXICOTE 03-084 should be stored in the original, unopened

and undamaged containers in a dry place at temperatures between 5°C and 30°C. Exposure to frost should be avoided.

HEALTH & SAFETY Please see separate Material Safety Data Sheet.

Issue No.2_March 2013

All information is given in good faith but without warranty. We cannot accept responsibility or liability for any damage, loss or patent infringement resulting from the use of this information.

Scott Bader Company Limited, Wollaston, Wellingborough, Northamptonshire, NN29 7RL

Telephone: +44 (0) 1933 663100 Facsimile: +44 (0) 1933 666529













