



# TEXICOTE<sup>®</sup> 57-0058

## Styrene homopolymer

### INTRODUCTION

TEXICOTE 57-0058 is an improved styrene homopolymer emulsion. It dries to a white powder below its high minimum film forming temperature.

Texicote 57-0058 is APEO free

### CHARACTERISTICS (Not to be taken as a specification)

Solids content	%	50
Viscosity at 25°C (Brookfield RVT Spindle 1, 20 rpm)	mPa s	70
pH		9.0
Specific Gravity at 25°C		1.03
Emulsifying system		Anionic
MFFT*	°C	105
Particle size	nm	300

\* Determined by metal bar with temperature gradient.

**APPLICATIONS**

TEXICOTE 57-0058 is a modifier for styrene/butadiene latices. It can be used to stiffen both non-woven or woven fabrics.

**PACKAGING**

TEXICOTE 57-0058 is supplied in 200 kg drums. Bulk supplies are delivered by road tanker.

**STORAGE**

TEXICOTE 57-0058 can be stored in the containers in which it is supplied.

Protect from frost.

**HEALTH & SAFETY**

Please see separate Material Safety Data Sheet.

Issue No. 3

Scott Bader Company Limited  
Wollaston, Wellingborough, Northamptonshire, NN29 7RL  
Telephone: +44 (0) 1933 663100 Facsimile: +44 (0) 1933 666529

