



TEXICRYL[®] 13-013

INTRODUCTION

The TEXICRYL[®] 13-013 is a water based dispersion of an externally plasticized acrylic/ styrene copolymer. This dispersion shows a high solid active matter, a very good waterproofing property and flexibility / elongation film

CHARACTERISTICS (Not to be taken as a specification)

Solids Content	%	54 - 56
Viscosity at 25°C (Brookfield RVT, Spindle 4, 100 rpm)	mPa s	800 - 2000
Particle size	nm	250
pH		7.5 - 9
Minimum film formation temperature	°C	0
Surfactant system (APEO free)		Anionic/Non-ionic

APPLICATIONS

Texicryl 13-013 can be compounded into coatings with a high degree of flexibility and water resistance for use in masonry, roof and floor. One major application is waterproofing membrane before ceramic tiles.

PACKAGING

Texicryl 13-013 is supplied in 120kg drums, 1 tonne IBC's or bulk supplies are delivered by road tanker.

STORAGE

Texicryl 13-013 may be stored in the containers in which it is supplied.
Protect from frost and extended exposure to direct sunlight.

HEALTH & SAFETY

Please see separate Material Safety Data Sheet.

Issue No.2

Scott Bader Company Limited
Wollaston, Wellingborough, Northamptonshire, NN29 7RL
Telephone: +44 (0) 1933 663100 Facsimile: +44 (0) 1933 666529

