

Crystic[®] VE 679PA

DCPD - Modified Vinyl Ester Resin for Skin Coats

Introduction

Crystic VE679PA is a pre-accelerated, thixotropic, DCPD modified, vinyl ester resin.

Applications

Crystic VE679PA was developed for use as a skin coat in marine and tooling applications.

Features and Benefits

Crystic VE679PA has excellent blister resistance and significantly reduces the occurrence of print through, to produce durable mouldings with an enhanced surface finish.

Approvals

Crystic VE679PA is approved by Lloyd's Register of Shipping for use in the construction of craft under their survey.

Formulation

Crystic VE679PA must be thoroughly stirred and allowed to attain workshop temperature (18°C - 20°C) before use. It needs only the addition of a catalyst to start the curing reaction. Either Norox[®] MEKP-925 H catalyst or Norox[®] KP9 catalyst can be used. This should be added at 2% into the resin. The geltime of Crystic VE679PA can be approximately determined from the table below.

N.B. Peroxide catalysts are highly reactive and may decompose with explosive violence, or cause fires, if they come into contact with flammable materials, metals or accelerators. For this reason they must never be stored in metal containers or be mixed directly with accelerators.

Pot Life

| Temperature | Pot Life in Minutes Using 2% Norox MEKP-925 H Catalyst | Pot Life in Minutes Using 2% Norox KP9 Catalyst |
|-------------|---|--|
| 15°C | 50 mins | 50 mins |
| 20°C | 28 mins | 34 mins |
| 25°C | 18 mins | 23 mins |

Additives

Adding pigment, fillers or other additives may adversely affect the resin properties. Users should consult Scott Bader's Technical Service Department before making any such additions.

Typical Properties

The following tables give typical properties of Crystic VE679PA when tested in accordance with the appropriate BS or BS EN ISO test method.

| Property | | Liquid Resin | |
|--|-------------------|---|-------|
| Appearance | | Red / Brown | |
| Viscosity at 25°C 37.35sec ⁻¹ | Poise | 3.5 | |
| Viscosity at 25°C 4500sec ⁻¹ | Poise | 2.3 | |
| Specific Gravity @ 25°C | gcm ⁻³ | 1.065 | |
| Stability in the dark at 25°C | months | 3 | |
| Geltime at 25°C using 2% Norox MEKP-925 H Catalyst | minutes | 18 | |
| Geltime at 25°C using 2% Norox KP9 Catalyst | Minutes | 23 | |
| Property | | Fully Cured Resin (unfilled casting) | |
| | | * | ** |
| Barcol Hardness (GYZJ 934 - 1) | | 23 | 35 |
| Deflection Temperature under load (1.80 MPa) | °C | 60 | 94 † |
| Water Absorption 24hrs @23°C | mg | 10 | 15 |
| Tensile Strength | MPa | 60 | 52 |
| Tensile Modulus | GPa | 2.7 | 3.0 |
| Elongation at Break | % | 4.3 | 2.1 |
| Specific Gravity @ 25°C | gcm ⁻³ | 1.161 | 1.158 |

* Curing Schedule - 24hrs @ 20°C, 16hrs @ 40°C

** Curing Schedule - 24hrs @ 20°C, 3hrs @ 80°C

† Curing Schedule - 24hrs @ 20°C, 5 hrs @ 80°C, 3 hrs @ 120°C

Storage

Crystic VE679PA should be stored in the dark in suitable closed containers. It is recommended that the storage temperature should be less than 20°C where practical, but should not exceed 30°C. Ideally, containers should be opened only immediately prior to use.

Packaging

Crystic VE679PA is supplied in 25kg and 200kg steel containers.

Health and Safety

Please see the applicable Material Safety Data Sheets, depending on the curing system used.

Technical Leaflet No 102.22SA
August 2013

Before you use this information, kindly verify that this data sheet is the latest version.

All information is given in good faith but without warranty. We cannot accept responsibility or liability for any damage, loss or patent infringement resulting from the use of this information.

SCOTT BADER COMPANY LIMITED

Scott Bader (Pty) Ltd
Reg. No. 93/00466/07
1 Lubex Road,
Hammarisdale
P.O. Box 1539, Hillcrest,
3650. South Africa
Tel: +27 (0) 31 736 8500
Fax: +27 (0) 31 736 8511

Gauteng
Broadacres Business
Centre
Cnr Cedar Rd and 3rd
Ave
Broadacres, Sandton
Tel: (011) 064 5673

KwaZulu Natal
1 Lubex Road,
Hammarisdale
Tel: (031) 736 8500

Eastern Cape
Freightpak Building
Chevrolet St
Markman Industrial
Port Elizabeth
Tel: (041) 409 783

Western Cape
Unit 4B
Tyger Lake
Niagara Way
Tyger Valley
Cape Town
Tel: (021) 914 6011

