



CRESTAKYD[®] 10-1022

Long oil air drying alkyd

INTRODUCTION CRESTAKYD 10-1022 is a fast drying alkyd that has excellent brushability & flow characteristics, as well as good gloss retention & weathering resistance.

CHARACTERISTICS (Not to be taken as a specification)

Appearance		clear, bit free
Solids content	%	70
Oil Type		linoleic
Oil content	%	67
Solvent		White Spirit
Acid value (base resin)	mgKOH g ⁻¹	10 max
Viscosity Brookfield, Spindle 4, 10 rpm @ 25°C	mPa·s	8000
50% NVC in white spirit, DIN 4 cup, @ 20°C	seconds	70-100
Colour	Gardner	6 max

APPLICATIONS CRESTAKYD 10-1022 can be used for economical decorative and do-it-yourself paints, including primers, topcoats, and varnishes.

PACKAGING

CRESTAKYD 10-1022 is supplied in drums. Bulk deliveries are by road tanker.

STORAGE

The resin should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 0°C and 30°C. Exposure to direct sunlight should be avoided.

HEALTH & SAFETY

Please see separate Material Safety Data Sheet.

Issue No.3

Scott Bader Company Limited
Wollaston, Wellingborough, Northamptonshire, NN29 7RL
Telephone: +44 (0) 1933 663100 Facsimile: +44 (0) 1933 666529

