



CRESTAKYD[®] 30-5042

Short oil air drying alkyd

INTRODUCTION CRESTAKYD 30-5042 is a fast drying short oil alkyd supplied in xylene for use in air-dry and force-dry primers and topcoats.

CHARACTERISTICS (Not to be taken as a specification)

Solids Content	%	60
Viscosity (PRS bubble tube)	mPa·s	3750
Oil length	%	40
Oil type		linoleic
Solvent		Xylene
Acid value (base resin)	mg KOH g ⁻¹	15 max
Colour	Gardner	8 max
Flash Point	°C	24

APPLICATIONS

CRESTAKYD 30-5042 is recommended for use in air dry and force dry primers and topcoats in a variety of general industrial metal coating applications.

PACKAGING

CRESTAKYD 30-5042 is supplied in drums. Bulk deliveries are by road tanker.

STORAGE

The resin should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 0°C and 30°C. Exposure to direct sunlight should be avoided.

HEALTH & SAFETY

Please see separate Material Safety Data Sheet.

Issue No. 2

Scott Bader Company Limited
Wollaston, Wellingborough, Northamptonshire, NN29 7RL
Telephone: +44 (0) 1933 663100 Facsimile: +44 (0) 1933 666529

