



# CRESTAKYD<sup>®</sup> 10-2020

## Long oil air drying alkyd

**INTRODUCTION** CRESTAKYD 10-2020 is a fast drying alkyd that has excellent brushability & flow characteristics, as well as good gloss retention & weathering resistance

**CHARACTERISTICS (Not to be taken as a specification)**

|   |                        |                      |
|---|------------------------|----------------------|
| Appearance  |                        | clear, bit free      |
| Solids content                                    | %                      | 60                   |
| Oil Type  |                        | linoleic             |
| Oil content                                       | %                      | 67                   |
| Solvent   |                        | White spirit 180/220 |
| Acid value (base resin)                           | mg KOH g <sup>-1</sup> | 10 max               |
| Viscosity<br>Brookfield, spindle 3, 20 rpm @ 25°C | mPa·s                  | 3250                 |
| Colour  | Gardner                | 6 max                |

**APPLICATIONS**

CRESTAKYD 10-2020 can be used for economical decorative and do-it-yourself paints, including primers, topcoats, and varnishes.

**PACKAGING**

CRESTAKYD 10-2020 can be supplied in drums. Bulk deliveries are by road tanker.

**STORAGE**

The resin should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 0°C and 30°C. Exposure to direct sunlight should be avoided.

**HEALTH & SAFETY**

Please see separate Material Safety Data Sheet.

Issue No. 3

Scott Bader Company Limited  
Wollaston, Wellingborough, Northamptonshire, NN29 7RL  
Telephone: +44 (0) 1933 663100 Facsimile: +44 (0) 1933 666529

