



# CRESTAKYD<sup>®</sup> 10-2033

## Long oil air drying alkyd

**INTRODUCTION** CRESTAKYD 10-2033 is a fast drying alkyd that has excellent brushability with good flow characteristics.

**CHARACTERISTICS (Not to be taken as a specification)**

Appearance		Clear bit free
Solids Content	%	60
Oil type		linoleic
Oil content	%	60
Solvent		White spirit 180/220
Acid value	mg KOH g <sup>-1</sup>	10 max
Viscosity Brookfield, Spindle 3, 10 rpm @ 25°C	mPa·s	4000
Colour	Gardner	6 max

**APPLICATIONS** CRESTAKYD 10-2033 can be used for economical decorative paints, primers and varnishes. It has excellent compatibility with “universal” colorants.

**PACKAGING**

CRESTAKYD 10-2033 is supplied in drums. Bulk tankers are by road tanker.

**STORAGE**

The resin should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 0°C and 30°C. Exposure to direct sunlight should be avoided.

**HEALTH & SAFETY**

Please see separate Material Safety Data Sheet.

Issue No. 3

Scott Bader Company Limited  
Wollaston, Wellingborough, Northamptonshire, NN29 7RL  
Telephone: +44 (0) 1933 663100 Facsimile: +44 (0) 1933 666529

