



CRESTAKYD[®] 20-5036

Medium oil air drying alkyd

INTRODUCTION CRESTAKYD 20-5036 is a chain stopped alkyd with excellent drying, gloss and weathering properties.

CHARACTERISTICS (Not to be taken as a specification)

Appearance		Clear, bit free
Solids content	%	65
Oil type		linoleic
Oil content	%	49
Solvent		Xylene
Acid value (base resin)	mg KOH g ⁻¹	max. 10
Viscosity, Brookfield, Spindle 3, 20 rpm @ 25°C	mPa·s	2750
Colour	Gardner	6 max

APPLICATIONS CRESTAKYD 20-5036 can be used for air-drying primers and industrial finishes.

PACKAGING CRESTAKYD 20-5036 can be supplied in drums. Bulk deliveries are by road tanker.

STORAGE

The resin should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 0°C and 30°C. Exposure to direct sunlight should be avoided.

HEALTH & SAFETY

Please see separate Material Safety Data Sheet.

Issue No. 2

Scott Bader Company Limited
Wollaston, Wellingborough, Northamptonshire, NN29 7RL
Telephone: +44 (0) 1933 663100 Facsimile: +44 (0) 1933 666529

