

# TEXICRYL® 13-066

## Styrene acrylic copolymer emulsion

#### INTRODUCTION

TEXICRYL 13-066 is a styrene acrylic copolymer emulsion, designed primarily for the production of flexible, water-resistant

ceramic tile adhesives.

TEXICRYL 13-066 is especially suitable for floor tile

adhesives.

TEXICRYL 13-066 is Alkyl Phenol Ethoxylate free.

### **CHARACTERISTICS** (Not to be taken as a specification)

Solids Content	%	50
Viscosity at 25°C (Brookfield RVT, Spindle 4, 100 rpm)	mPa s	700
pH		8
Particle size	nm	200
MFFT*	°C	0

<sup>\*</sup> Determined by metal bar with temperature gradient.

#### **APPROVAL**

C.T.A.'s formulated on this product can achieve class AA

standard to BS 5980: 1980 and BS EN 1324.99

**APPLICATIONS** TEXICRYL 13-066 can be compounded into adhesives with a

high degree of flexibility for use with wall and floor ceramic

tiles.

**PACKAGING** TEXICRYL 13-066 is supplied in 200 kg drums, 1 tonne IBC's

or bulk supplies are delivered by road tanker.

**STORAGE** TEXICRYL 13-066 may be stored in the containers in which it

is supplied.

Protect from frost and extended exposure to direct sunlight.

**HEALTH & SAFETY** Please see separate Material Safety Data Sheet.

Issue No.2











