



TEXICRYL[®] 13-078

Styrene acrylic copolymer emulsion

INTRODUCTION

TEXICRYL 13-078 is a styrene acrylic copolymer emulsion, designed primarily as a binder for high performance ceramic tile adhesives.

TEXICRYL 13-078 is Alkyl Phenol Ethoxylate free.

CHARACTERISTICS (Not to be taken as a specification)

Solids Content	%	50
Viscosity at 25°C (Brookfield RVT, Spindle 4, 100 rpm)	mPa s	100
pH		8
Particle size	nm	200
Minimum film formation temperature*	°C	18
Glass Transition Temperature	°C	20

* Determined by metal bar with temperature gradient.

APPROVALS

C.T.A.'s formulated on this product can achieve EN 12004 : 2001 D2 classification.

APPLICATIONS

Texicryl 13-078 has been designed to be formulated with a wide range of filler types into water resistant tile adhesives and fix and grouts.

PACKAGING

Texicryl 13-078 is supplied in 200 kg drums, 1 tonne IBC's or bulk supplies are delivered by road tanker.

STORAGE

Texicryl 13-078 may be stored in the containers in which it is supplied.

Protect from frost and extended exposure to direct sunlight.

HEALTH & SAFETY

Please see separate Material Safety Data Sheet.

Issue No. 2

Scott Bader Company Limited
Wollaston, Wellingborough, Northamptonshire, NN29 7RL
Telephone: +44 (0) 1933 663100 Facsimile: +44 (0) 1933 666529

