



TEXICRYL® 13-692 Styrene acrylic copolymer

INTRODUCTION

TEXICRYL 13-692 is an APEO free Styrene Acrylic copolymer emulsion, designed primarily for the production of flexible, water-resistant ceramic tile adhesives.

TEXICRYL 13-692 is especially suitable for floor tile adhesives.

CHARACTERISTICS

(Not to be taken as a specification)

Solids content	%	50 ± 1
Viscosity at 25°C	mPa s	850
(Brookfield RVT,		
Spindle 4, 100 rpm)		
pH		7.5 - 8.5
Particle size	nm	200
Emulsifying system		Anionic
MFFT*	°C	0

^{*} Determined by metal bar with temperature gradient.

APPROVALS

C.T.A.'s formulated on this product can achieve class AA standard to BS 5980: 1980

APPLICATIONS

TEXICRYL 13-692 can be compounded into adhesives with a high degree of flexibility for use with wall and floor ceramic tiles.

For more detailed information please ask for booklet no. CTA01.

PACKAGING TEXICRYL 13-692 is supplied in 200 kg drums. Bulk supplies are

delivered by road tanker.

STORAGE TEXICRYL 13-692 may be stored in the containers in which it is

supplied.

Protect from frost.

HEALTH & SAFETY Please see separate Material Safety Data Sheet.

Issue No. 2.16 Feb 2012





SCOTT BADER (Pty) Ltd Reg. No. 93/0046/607
1 Lubex Road, Hammarsdale
P.O. Box 1539, Hillcrest, 3650
South Africa
Telephone: +27 (0) 31 736 8500
Telefax: +27 (0) 31 736 8511